JUN-16-2006 FRI 17:25

Customer No.: 31561 Application No.: 10/709,989

Docket No.: 12960-US-PA

To the specification:

[0037] Referring to FIG. 1, the cold cathode fluorescent flat lamp (CCFFL) 100

comprises, for example but not limited to, a cavity 102, a discharge gas 104, a

fluorescence material 106, first electrode pairs 108 and second electrode pairs 110,

wherein the first electrode pairs 108 are separated from the second electrode pairs 110.

The cavity 102 comprises a first inner wall and a second inner wall opposite to the first

inner wall. In the present embodiment, the cavity 102 comprises, for example but not

limited to, a first substrate 112, a second substrate 114 disposed over the first substrate

112 and a side bar 116 connected to an edge of the first substrate 112 and an edge of the

second substrate 114. Therefore, in the present embodiment, the first inner wall may

be the first substrate 112, and the second inner wall may be the second substrate 114.

[0039] The first electrode pairs 108 is disposed over the first inner wall of the cavity

102, for example but not limited to, over the first substrate 112. For example, each of

first electrode pairs 108 comprises a first anode 120 (as the "+" shown in FIG. 1) and a

first cathode 130 (as the "-" shown in FIG. 1). In one embodiment of the invention, the

first anodes 120 and the second cathodes 130 are arranged in a sequence in the order of

anode, cathode, cathode and anode over the first substrate 112 as shown in FIG. 1.

The second electrode pair 110 is disposed over the second inner wall of the cavity 102,

7

PAGE 8/12 \* RCVD AT 6/16/2006 5:22:12 AM [Eastern Daylight Time] \* SVR:USPTO-EFXRF-1/10 \* DNIS:2738300 \* CSID: \* DURATION (mm-ss):03-28

JUN-16-2006 FRI 17:25 FAX NO. P. 09/18

Customer No.: 31561 Application No.: 10/709,989

Docket No.: 12960-US-PA

for example but not limited to, over the second substrate 114. Each second electrode

pair 110 may comprise a second anode 122 and a second cathode 132. Alternatively,

the first electrode pairs 108 and the second electrode pair 110 may be disposed over an

outer wall of the cavity 102 (as shown in dash line in FIGS 1 and 2). In one

embodiment of the invention, a sequence of arranging the second anodes 122 and the

second cathodes 132 over the second substrate 114 is similar or identical to a sequence

of arranging the first anodes 120 and second cathodes 130 over the first substrate 112

described above.